

BHARAT FLAMEPROOF MANUFACTURING INDUSTRY

World Class Flameproof Equipments



B.F.M.I

We Aims to Give Protection



World Class Flameproof Equipments



CIMFR

एन एस आई सी
NSIC



BIS



www.bharatflameproof.com

VISION

To be a leading & Innovative company in the field of renewable energy sources and Lighting Solutions.

MISSION

To provide most eco friendly energy efficient products with reliable in quality, safe to use and at affordable price which makes our customers life simple and comfortable. With our innovative products and solutions we want to contribute to the development of our society.

INDEX

1 LUMINARIES

2 CONTROL STATION

3 JUNCTION BOX

4 PANEL

5 DISTRIBUTION BOARD

6 INSTRUMENTATION PANLE

7 CLEAN ROOM APPLICATION

8 FAN

9 ASSCERIERS

10 CUSTOMER SPECIFIED ITEM



FLAMEPROOF FIRE ALARM/MANUAL CALL POINT



Material:Cast Aluminium Alloy LM6.
 Flameproof: Zone 1 & 2,
 GAS GROUP:IIA,IIB,IIC
 Weatherproof:IP 66
 Finish:red color
 Gasket:Neoprene
 Cable Entry:2 Nos. 3/ 4" ET Entry

FLAMEPROOF HOOTER WITH FLASHER



Material:Cast Aluminium Alloy LM6.
 Flameproof: Zone 1 & 2,
 GAS GROUP:IIA,IIB,IIC
 Weatherproof:IP 66
 Finish:Light Grey to Shade 631
 Gasket:Neoprene
 Cable Entry:2 Nos. 3/ 4" ET Entry.
 Noise Level:120db.

FLAMEPROOF LIMIT SWITCH (ROLLER/LEVER TYPE)



Material:Cast Aluminium Alloy LM6.
 Flameproof: Zone 1 & 2,
 Gas group:IIC
 Weatherproof:IP 65
 Finish:Light Grey to Shade 631
 Gasket:Neoprene
 Cable Entry:1 Nos. 3/4" ET Entry.
 Limit Switch: 1NO+1NC, 10A 500V

FLAMEPROOF STOP PUSH BUTTON STATION



Type of protection: Ex-d
 Material:Cast Aluminium Alloy LM6.
 Flameproof: Zone 1 & 2,
 GAS GROUP:IIA,IIB,IIC
 Weatherproof:IP 66
 Finish:Light Grey to Shade 631
 Gasket:Neoprene
 Cable Entry:2 Nos. 3/4" ET Entry.

FLAMEPROOF PUSH BUTTON STATION R/F/S



Material:Cast Aluminium Alloy LM6.
 Flameproof: Zone 1 & 2
 Gas Group:IIA,IIB,IIC
 Weatherproof:IP 66
 Finish:Light Grey to Shade 631
 Gasket:Neoprene
 Cable Entry:2 Nos. 3/4" ET Entry.
 Forward PB: Green Colour-NO CONTRACT
 Reverse PB: Yellow Colour, - NO CONTRACT

FLAMEPROOF START/STOP PUSH BUTTON STATION



Material:Cast Aluminium Alloy LM6.
 Flameproof: Zone 1 & 2,IIA,IIB,IIC
 as per IS/IEC 60079-1:2007
 Weatherproof:IP 66 as per IS/IEC 60529:2001
 Finish:Light Grey to Shade 631 of IS:5 (Epoxy Powder Coated)
 Gasket:Neoprene
 Cable Entry:2 Nos. 3/4" ET Entry.
 Start PB:Green Colour, Momentary Type



FLAMEPROOF PUSH BUTTON STATION WITH INDICATION LAMP



Material:Cast Aluminum Alloy LM6.
 Flameproof: Zone 1 & 2,IIA,IIB,IIC
 as per IS/IEC 60079-1:2007
 Weatherproof:IP66 as per IS/IEC 60529:2001
 Finish:Light Grey to Shade 631 of IS:5
 (Epoxy Powder Coated)
 Gasket:Neoprene, Cable Entry:2 Nos. 3/4" ET Entry.
 Start PB: Green Colour, Momentary Type
 Stop PB: Red Colour, Mushroom Head,
 Pad Lockable or Key Lockable type
 Indicating Lamp: Red colour for ON indication

FLAMEPROOF ON/OFF ROTARY SWITCH



Material:Cast Aluminium Alloy LM6.
 Flameproof: Zone 1 & 2,IIA,IIB,IIC as per IS/IEC 60079-1:2007
 Weatherproof:IP 66 as per IS/IEC 60529:2001
 Finish:Light Grey to Shade 631 of IS:5 (Epoxy Powder Coated)
 Gasket:Neoprene
 Cable Entry:2 Nos. 3/4" ET Entry.
 Switch: 16A/32AMP/25AMP DP
 ON/OFF Rotary Switch

FLAMEPROOF SWITCH SOCKET COMBINE



Material: Cast Aluminium Alloy LM6.
 Flameproof: Zone 1 & 2,
 GAS GROUP:IIA,IIB,IIC
 Weatherproof: IP 66
 Finish: Light Grey to Shade 631
 Gasket: Neoprene
 Cable Entry:2 Nos. 3/4" ET Entry.
 Switch: 16A/25AMP/32AMP Switch
 RATING: 230VOLT /415 VOLT
 Pin: 3 PIN (2P+E) 4 PIN (3P+E),5 PIN(4P+E)

FLAMEPROOF TEMPERATURE INDICATOR



Material:Cast Aluminium Alloy LM6.
 Flameproof: Zone 1 & 2,IIA,IIB,IIC as per IS/IEC 60079-1:2007
 Weatherproof:IP 66 as per IS/IEC 60529:2001
 Finish:Light Grey to Shade 631 of IS:5 (Epoxy Powder Coated)
 Gasket:Neoprene
 Cable Entry:2 Nos. 3/4" ET Entry.
 RANGE :0 TO 200 DEGREE , 0 TO 400 DEGREE

FLAMEPROOF REACTOR VESSEL LAMP



Type of protection: Ex-d
Material: Cast Aluminium Alloy LM6
Flameproof: Zone 1 & 2
Gas Group: IIA,IIB
Finish: Light Grey to Shade 631
Glass: Heat Resistant Toughened
Cable Entry: 2 Nos. 3/4" ET Entry.

FLAMEPROOF BULK HEAD LIGHT FITTING



Type of protection: Ex-d
Material: Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2, Gas group: IIA,IIB
Finish: Light Grey to Shade 631 of IS:5
Glass: Heat Resistant Toughened Type
Lamp Holder: ES Holder.
Cable Entry: 2 Nos. 3/4" ET Entry.
Lamp Rating: 160W MLL, 125W HPMV,
23W CFL,20W LED,40 W LED

FLAMEPROOF CLEAN ROOM FITTING 2 X 36



Type of protection: Ex-d
Material: Cast Aluminium Alloy LM6
Flameproof: Zone 1 & 2
Gas Group: IIA,IIB
Finish: Light Grey to Shade 631
Glass: Heat Resistant Toughened Type-A
Lamp Holder: ES Holder
Cable Entry: 2 Nos. 3/4" ET Entry.
Lamp Rating (Integral type: 2 X 36 W PL TUBE,
40 W LED,60 W LED SUPPLY 230 V AC

FLAMEPROOF AVIATION LIGHT



Type of protection: Ex-d
Material: Cast Aluminium Alloy LM6
Flameproof: Zone 1 & 2
Gas Group: IIA,IIB
Finish: Light Grey to Shade 631
Glass: Heat Resistant Toughened Type-A
Cable Entry: 2 Nos. 3/4" ET Entry.

FLAMEPROOF FLOOD LIGHT FITTING



Material: Cast Aluminum Alloy LM6.
Flameproof: Zone 1 & 2,
Gas Group: IIA, IIB, IIC
Weatherproof: IP 66
Finish: Light Grey to Shade 631
Gasket: Neoprene
Glass: Heat Resistant Toughened
Lamp Holder: ES Holder.
Cable Entry: 2 Nos. 3/4" ET Entry
Led rating: 100W,120W,150W,200W

FLAMEPROOF HAND LAMP



Material: Cast Aluminum Alloy LM6.
Flameproof: Zone 1 & 2 ,
Gas group: IIA,IIB,IIC
Weatherproof: IP 66
Finish: Light Grey to Shade 631
Gasket: Neoprene
Glass: Heat Resistant Toughened
Lamp Holder: ES Holder.
Cable Entry: 1 Nos. 3/4" ET Entry.
Lamp Rating: 15W CFL,100W GLS,10W LED

FLAMEPROOF SUNFLOWER LED LIGHT FITTING



Material: Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,
Gas Group: IIA,IIB,IIC
Weatherproof: IP 66
Finish: Light Grey to Shade 631
Gasket: Neoprene
Glass: Heat Resistant Toughened
Cable Entry: 2 Nos. 3/4" ET Entry.
Lamp Rating (Integral type): 25 W LED,
45 W LED, 55 W LED, 60 W LED

FLAMEPROOF TOWER LAMP



Type of protection: Ex-d
Material: Cast Aluminium Alloy LM6
Flameproof: Zone 1 & 2
GAS GROUP: IIA,IIB
Finish: Light Grey to Shade 631
Glass: Heat Resistant Toughened Type-A
Lamp Holder: ES Holder
Cable Entry: 2 Nos. 3/4" ET Entry.

FLAMEPROOF TUBE LIGHT FITTING



Type of protection: Ex-d
Material: Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,
Gas Group: IIB, Weatherproof: IP 65
Finish: Light Grey to Shade 631 ,
Gasket: Neoprene
Glass: Heat Resistant Toughened Type-A
Lamp Holder: Pin type Holder.,
Cable Entry: 2 Nos. 3/4" ET Entry.
Lamp Rating: 1x40W,1x36W CFL,1x28W T5,1x22W LED
2x40W,2x36W CFL,2x28W T5,2x22W LED

FLAMEPROOF WELL GLASS FITTING DOME TYPE



Material: Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,, Gas Group: IIA,IIB,IIC
Weatherproof: IP 66, Finish: Light Grey to Shade 631
Gasket: Neoprene, Lamp Holder: ES Holder.
Glass: Heat Resistant Toughened Type-A
Cable Entry: 2 Nos. 3/4" ET Entry.
Lamp Rating (Integral type):
160W M LL, 45W CFL, 25W CFL
Lamp Rating (Integral type): 80W HPMV,
125W HPMV, 70W MH, 150MHL
Led Rating: 35W, 45W, 55W, 60W
Supply: 230VAC

FLAMEPROOF JUNCTION BOX (GAS GROUP-IIA, IIB) MULTIPLE WAY



Material: Cast Aluminum Alloy LM6.
 Flameproof: Zone 1 & 2, Gas group: IIA, IIB,
 Weatherproof: IP 66, TEMP CLASS: T6
 Finish: Light Grey to Shade 631
 Gasket: Neoprene, Cable Entry: as per request
 Box size: 300MM X 300 MM X150MM
 380MM X 380 MM X 150MM
 470MM X 470MM X 150MM
 760MM X 530 MM X150MM
 INNER DEPTH: 150MM, 240MM, 300MM

FLAMEPROOF JUNCTION BOX (GAS GROUP-IIIC) MULTIPLE WAY



Material: Cast Aluminum Alloy LM6.
 Flameproof: Zone 1 & 2, Gas group: IIA, IIB, IIC
 Weatherproof: IP 66, Finish: Light Grey to Shade 631
 Gasket: Neoprene, Cable Entry: as per client request
 Box size: 175MM X 175 MM X120MM
 275MM X 275 MM X 150MM
 375MM X 375MM X 150MM
 500MM X 500 MM X150MM
 INNER DEPTH: 150MM, 200MM, 250MM

FLAMEPROOF ANNUNCIATOR PANEL (4 TO 24 WINDOWS)



Material: Cast Aluminium Alloy LM6.
 Flameproof: Zone 1 & 2,
 Gas group: IIA, IIB
 Weatherproof: IP 65
 Finish: Light Grey to Shade 631
 Gasket: Neoprene
 Cable Entry: As per Customer Request

FLAMEPROOF AUTOMATION CONTROLLER PANEL



Material: Cast Aluminum Alloy LM6.
 Flameproof: Zone 1 & 2,
 GAS GROUP: IIA, IIB
 Weatherproof: IP 66
 Temp CLASS: T6
 Finish: Light Grey to Shade 631
 Gasket: Neoprene
 Cable Entry: As per Customer Request

FLAMEPROOF CONTROL PANEL



Material: Cast Aluminium Alloy LM6.
 Flameproof: Zone 1 & 2,
 GAS GROUP: IIA, IIB
 TEMP CLASS: T6
 Weatherproof: IP 66
 Finish: Light Grey to Shade 631
 Gasket: Neoprene
 Cable Entry: As per Customer Request

FLAMEPROOF DATA LOGGER PANEL



Material: Cast Aluminum Alloy LM6.
 Flameproof: Zone 1 & 2,
 GAS GROUP: IIA, IIB
 TEMP CLASS: T6
 Weatherproof: IP 66
 Finish: Light Grey to Shade 631
 Gasket: Neoprene
 Cable Entry: As per Customer Request

FLAMEPROOF STAR DELTA STARTER PANNEL



Material: Cast Aluminum Alloy LM6.
 Flameproof: Zone 1 & 2
 Gas group: IIA, IIB,
 Weatherproof: IP 66
 Temp class: T6
 Finish: Light Grey to Shade 631
 Gasket: Neoprene
 Cable Entry: As per your requirement

FLAMEPROOF HMI AUTOMATION PANEL



MATERIAL: CAST ALUMINUM ALLOY LM6.
 FLAMEPROOF: ZONE 1 & 2,
 GAS GROUP: IIA, IIB
 TEMP CLASS: T6
 WEATHERPROOF: IP 66
 FINISH: LIGHT GREY TO SHADE 631
 GASKET: NEOPRENE
 CABLE ENTRY: AS PER CUSTOMER REQUEST

FLAMEPROOF MOTOR CONTROL PANEL



Material: Cast Aluminum Alloy LM6.
 Flameproof: Zone 1 & 2,
 GAS GROUP: IIB
 Weatherproof: IP 65
 Finish: Light Grey to Shade 631
 Gasket: Neoprene
 Cable Entry: As per Customer Request
 RATING : 3 HP, 5 HP, 7.5 HP X 3 NOS
 STARTER IN ONE PANEL

FLAMEPROOF PCL PANEL ENCLOSURE



Material: Cast Aluminium Alloy LM6.
 Flameproof: Zone 1 & 2,
 GAS GROUP: IIB
 TEMP CLASS: T6
 Weatherproof: IP 66
 Finish: Light Grey to Shade 631
 Gasket: Neoprene
 No. of Feeders: As per Customer Request
 Cable Entry: As per Customer Request

FLAMEPROOF VACCUM CONTROL PANEL



Material: Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP: IIB
TEMP CLASS: T6
Weatherproof: IP 66
Finish: Light Grey to Shade 631
Gasket: Neoprene
No. of Feeders: As per Customer Request
Cable Entry: As per Customer Request

FLAMEPROOF VFD PANEL



Material: Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP: IIB
Weatherproof: IP 65
Finish: Light Grey to Shade 631
Gasket: Neoprene
No. of Feeders: As per Customer Request
Cable Entry: As per Customer Request

FLAMEPROOF 12/18/24/36 WAY LIGHTING / POWER DISTRIBUTION BOARD



Material: -Cast Aluminum Alloy LM6.
Flameproof: -Zone 1 & 2
Gas group: -IIA, IIB, IIC
Weatherproof: -IP 66 as per
IS/IEC 60529:2001
Finish: -Light Grey to Shade 631
Gasket: -Neoprene

FLAMEPROOF TEMP CONTROLLER



Material: Cast Aluminum Alloy LM6.
Flameproof: Zone 1 & 2
Gas group: IIA, IIB, IIC
Weatherproof: IP 65
Finish: Light Grey to Shade 631
Gasket: Neoprene
Cable Entry: 3 Nos. 3/4" ET Entry.

FLAMEPROOF INSTRUMENT ENCLOSURE



Material: -Cast Aluminium Alloy LM6.
Flameproof: -Zone 1 & 2,
GAS GROUP: - IIB, IIC
Weatherproof: -IP 65
Finish: Light Grey to Shade 631
Gasket: Neoprene
Cable Entry: As per Customer Request

FLAMEPROOF DOL STARTER



Material: Cast Aluminum Alloy LM6.
Flameproof: Zone 1 & 2
Gas group: IIA, IIB, IIC
Weatherproof: IP 65
Finish: Light Grey to Shade 631
Gasket: Neoprene
Cable Entry: 3 Nos. 3/4" ET Entry.

FLAMEPROOF CLEAN ROOM PUSH BUTTON STATION ON /OFF



Material: Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2, IIA, IIB, IIC
as per IS/IEC 60079-1:2007
Weatherproof: IP 66 as per IS/IEC 60529:2001
Finish: Light Grey to Shade 631 of IS:5 (Epoxy Powder Coated)
Gasket: Neoprene
Cable Entry: 2 Nos. 3/4" ET Entry.
Start PB: Green Colour, Momentary Type

FLAMEPROOF CLEAN ROOM ROTARY SWITCH



Material: Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP: IIA, IIB, IIC
Weatherproof: IP 66
Finish: Light Grey to Shade 631 of IS:5 (Epoxy Powder Coated)
Gasket: Neoprene
Cable Entry: 2 Nos. 3/4" ET Entry.
Switch: 16A/25A/32A DP ON/OFF Rotary Switch

FLAMEPROOF CLEAN ROOM BULK HEAD LIGHT FITTING



Material: Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,
Gas group: IIA, IIB
Finish: Light Grey to Shade 631 of IS:5
Glass: Heat Resistant Toughened Type
Lamp Holder: ES Holder.
Cable Entry: 2 Nos. 3/4" ET Entry.
Lamp Rating: 160W MLL, 125W HPMV,
23W CFL, 20W LED, 40 W LED
BOX : STAINLESS STEEL COVER PLATE/ MS BOX

FLAMEPROOF CLEAN ROOM SWITCH SOCKET COMBINE



Material: Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP: IIA, IIB, IIC
Weatherproof: IP 66
Finish: Light Grey to Shade 631
Gasket: Neoprene
Cable Entry: 2 Nos. 3/4" ET Entry.
Switch: 16A/25AMP/32AMP Switch
RATING: 230VOLT /415 VOLT
Pin: 3 PIN (2P+E) 4 PIN (3P+E), 5 PIN (4P+E)
BOX : STAINLESS STEEL COVER PLATE/ MS BOX

FLAMEPROOF EXHAUST FAN



Material:Cast Aluminium Alloy LM6.
Flameproof: IIB
Weatherproof:IP 55
Finish:Light Grey to Shade 631
Size:12" to 36"
Motor Rating:240 / 415 Volts AC,
RPM:1440 RPM, 50Hz

FLAMEPROOF PEDESTAL FAN



Certification Code: Exd, IIA, And IIB
Zone: 1 & 2
Protection: IP66
Temperature Classification: T6

FLAMEPROOF WALL MOUNTED FAN



Zone : 1 & 2
Gas group:IIA,IIB ,IIC
Temp Class : T6
FAN SIZE:16 INCH, 18 INCH,24 INCH,
RATING 230V AC,415V AC
MOTOR RPM :1440
HP :0.25 HP,0.50HP

FLAMEPROOF DOUBLE COMPRESSION CABLE GLAND/ DUMMY PLUG / PVC RUBBER HOOD



Material:
MS, Brass,and stainless steel
Flameproof:
Zone 1 & 2
Gas group: IIB
Weatherproof: IP 66

Size: 3/4" to 3" BSC Thread 1/2" to 2 1/2" NPT

FLAMEPROOF DIRECT ENTRY CONTROL STATION



Material:Cast Aluminum Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP:IIA,IIB,IIC
Weatherproof:IP 66
Finish:Light Grey to Shade 631
Gasket:Neoprene
Cable Entry:4 Nos. 3/4" ET Entry.



FLAMEPROOF CAMERA HOUSING



Resolution : 1000TVL, 1MP, 1.3MP, 2MP, 3MP
Vision: Day Night
Lens: Fixed Type -6mm/8mm/12mm/16mm
Meter Range:30mtr/40mtr/50mtr/80mtr
Voltage Supply:12V DC, Classification:Zone 1, Zone 2
Gas Group:I,IIA,IIB,IIC
Temperature Classification:T6
IP Protection:IP66
Cable Entry:02 Nos for M20(3/4"ET)
Hardware:Stainless Steel

FLAMEPROOF CLOCK DIGITAL



Gas group: IIA, IIB , Zone: 1 & 2
Temperature Classification: T6, Color:Siemens Gray
Material Die Cast Aluminum
Type: Stand Alone.& Master / Slave
Display: 4 Inch Red FND
Time Format: Hours & Minute with Battery Backup
Operating Voltage230 VAC, Frequency50 Hz
Enclosure Approved ByCMRI Dhanbad
Enclosure Size510 (W)*300(H)*140(D) mm
Display Window Size385 (W)*215(H) mm

FLAMEPROOF DOOR INTERLOCKING SYSTEM



Material:Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP:IIA,IIB
Finish:Light Grey to Shade 631
Gasket:Neoprene
Cable Entry:2 Nos. M16" ET Entry.

FLAMEPROOF GAS DETECTOR ENCLOSURE



Material:Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP:IIA,IIB,IIC
Weatherproof:IP 66
Finish:Light Grey to Shade 631
Gasket:Neoprene
Cable Entry:4 Nos. 3/4" ET Entry

FLAMEPROOF HEATER ENCLOSURE



Material:Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP:IIA,IIB,IIC
Weatherproof:IP 66
Finish:Light Grey to Shade 631
Gasket:Neoprene
Cable Entry:2 Nos. 3/4" ET Entry.

FLAMEPROOF M SHAPE TUBULAR HEATER PANEL



MATERIAL: CAST ALUMINUM ALLOY LM6.
FLAMEPROOF: ZONE 1 & 2,
GAS GROUP: IIA,IIB,
FINISH: LIGHT GREY TO SHADE 631
CABLE ENTRY: AS PER REQUIREMENT

FLAMEPROOF MAGNET



Material: Cast Aluminum Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP: IIA,IIB,
Finish: Light Grey to Shade 631
Gasket: Neoprene
OPERATING VOLTAGE:12VDC
CURRENT DRAW :500mA
Holding force:upto 600 lbs
Cable Entry:M12 -1 NOS

FLAMEPROOF PASS BOX



Material: Cast Aluminum Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP: IIA,IIB,
Finish: Light Grey to Shade 631
Gasket: Neoprene
Temp class: t6

FLAMEPROOF THERMOCOUPLE HEADS/ SENSOR



Material: Cast Aluminum Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP: IIA,IIB
Finish: Light Grey to Shade 631
Gasket: Neoprene
Cable Entry: 1 Nos. 3/4" ET Entry



FLAMEPROOF UV TUBE LIGHT FITTING



Material:Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP:IIB
Weatherproof: IP 65
Finish: Light Grey to Shade 631
Gasket: Neoprene
Glass: Heat Resistant Toughened Type-A
Cable Entry: 1 Nos. 3/4" ET Entry.
Size:1 foot/2 foot

FLAMEPROOF WEIGHING SCALE UNIT



Material:Cast Aluminium Alloy LM6.
Flameproof: Zone 1 & 2,
GAS GROUP:IIA,IIB
Finish:Light Grey to Shade 631
Gasket:Neoprene
Cable Entry:4 Nos. 3/4" ET Entry

FLAMEPROOF JUNCTION BOX 2/3/4 WAY



Material: Cast Aluminum Alloy LM6.
Flameproof: Zone 1 & 2, Gas group: IIA, IIB,
Weatherproof: IP 66, TEMP CLASS: T6
Finish: Light Grey to Shade 631
Gasket: Neoprene, Cable Entry: as per request

FLAMEPROOF EMERGENCY EXIT LIGHT FITTING



Type of protection- Ex-d
Material - Cast Aluminum Alloy Lm6
Flameproof - Zone 1 & 2
Gas group - IIA,IIB,IIC
Light specification - Maintained
1.5 hrs. Backup
5 W LED
Ni-Mh, Ni-Cd Rechargeable Battery
10 to 12 hrs. Recharging Period
Constant Voltage Charger

 Plot No B-21 MIDC, Industrial Area Phase –I, Dombivli (E)
Pin Code-421301, Dist. Thane, State Maharashtra

 bharatflameproof@gmail.com/sale@bharatflameproof.com

 www.bharatflameproof.com

 8108032323 / 9867202323 / 9372058489

 0251-2952934